



SPECIFICATIONS:

- Current Rating: 3.0 AMP
- Contact Resistance: 10mΩ Max
- Insulation Resistance: 1000MΩ Min
- Withstand Voltage: 600V AC/minute
- Operation Temperature: -40°C to +105°C

MATERIALS:

- Contact Material: Brass(H59-3)
- Contact Plating: Gold or Tin over 50u" Ni
- Insulator Material: Polyester(UL94V-0)

Ordering Code

- ① Series No.: 131 XX X X 3
- ② Number of Contacts: 01 Pin~80 Pin
- ③ Dip Spacing: 1=Single row, 2=Double row
- ④ Material Type: 1=PB/T/White, 2=PPS/Black
- ⑤ Insulator Height: 3=3.0mm
- ⑥ Contact Plated: 1=Gold flash, 2=Gold 3u", 3=Gold 5u", 4=Gold 10u", 5=Gold 15u", 6=Gold 30u", 7=Tin 200u"
- ⑦ Pin Length: L=XXXX
- ⑧ Tial & Mounting Style: S=Straight DIP Type, R=Right Angle DIP Type, M=Straight SMT Type
- ⑨ 1=SIP Socket, 2=Pin Connectors

- ① Series No.: 131=2.54 Pitch
- ② Number of Contacts: 01 Pin~80 Pin
- ③ Dip Spacing: 1=Single row, 2=Double row
- ④ Material Type: 1=PB/T/White, 2=PPS/Black
- ⑤ Insulator Height: 3=3.0mm
- ⑥ Contact Plated: 1=Gold flash, 2=Gold 3u", 3=Gold 5u", 4=Gold 10u", 5=Gold 15u", 6=Gold 30u", 7=Tin 200u"
- ⑦ Pin Length: L=XXXX
- ⑧ Tial & Mounting Style: S=Straight DIP Type, R=Right Angle DIP Type, M=Straight SMT Type
- ⑨ 1=SIP Socket, 2=Pin Connectors



深圳市联益电子有限公司
 HTTP://WWW.LYCONN.COM

E		Units	mm	Scale	2:1	Drawing By	Date
D		Tolerance Unless		Otherwise Specified		Check By	Date
C		X ~ ±0.30				Date	2007/03/02
B		.XX ~ ±0.25				Sheet	1 of 1
A		.XXX ~ ±0.20		Angle ~ ±3°		Title	2.54X3.0双头针座/180度系列
REV ZONE		LTR		DESCRIPTION		Drawing No.	IC2540-026-A2
1		2		3		File Path	
						REV	A

F

F

D

Δ

C

B

A

1 2 3 4 5 6 7 8