



SPECIFICATIONS:
 Current Rating: 3.0 AMP
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstand Voltage: 600V AC/minute
 Operation Temperature: -40°C to +105°C

MATERIALS:
 Contact Material: Brass(H59-3)
 Contact Plating: Gold or Tin over 50u" Ni
 Insulator Material: Polyester(UL94V-0)

Ordering Code

① 131 ② XX ③ X ④ X ⑤ X ⑥ X ⑦ XXXX ⑧ H ⑨ 2

- ① Series No. :
131=2.54 Pitch
- ② Number of Contacts:
01 Pin~80 Pin
- ③ Dip Spacing:
1=Single row
2=Double row
- ④ Material Type:
1=PBT/White
2=PPS/Black
- ⑤ Insulator Height:
3=3.0mm
- ⑥ Contact Plated
1=Gold flash
2=Gold 3u"
3=Gold 5u"
4=Gold 10u"
5=Gold 15u"
6=Gold 30u"
7=TiN 200u"
- ⑦ Pin Length:
L=XXXX
- ⑧ Tial & Mounting Style:
S=Strait DIP Type
R=Right Angle DIP Type
M=Strait SMT Type
H=Horizontal surface mount
- ⑨ 1=Socket
2=Pin Connectors

E		Units	mm	Scale	3:1	Drawing By	Date
D		Tolerance Unless Otherwise Specified					
C		Check By					
B		Date					
A		Date					
REV ZONE		LTR	DESCRIPTION	ECN.NO.	Date	Approval By	Date
1		1	2	3	4	5	6
F		Units		Scale	3:1	Drawing By	Date
E		Tolerance Unless Otherwise Specified					
D		Check By					
C		Date					
B		Date					
A		Date					
REV ZONE		LTR	DESCRIPTION	ECN.NO.	Date	Approval By	Date
1		1	2	3	4	5	6
F		Units		Scale	3:1	Drawing By	Date
E		Tolerance Unless Otherwise Specified					
D		Check By					
C		Date					
B		Date					
A		Date					
REV ZONE		LTR	DESCRIPTION	ECN.NO.	Date	Approval By	Date
1		1	2	3	4	5	6
F		Units		Scale	3:1	Drawing By	Date
E		Tolerance Unless Otherwise Specified					
D		Check By					
C		Date					
B		Date					
A		Date					
REV ZONE		LTR	DESCRIPTION	ECN.NO.	Date	Approval By	Date
1		1	2	3	4	5	6

LYCON

深圳市联益电子有限公司
 HTTP://WWW.LYCONN.COM

2.54mm 双头针 / 卧贴系列

Date: 2008/06/11
 Sheet: 1 of 1
 Title: 2.54mm 双头针 / 卧贴系列
 Drawing No.: IC-ST254-M1276-045
 File Path:

8